

Climate and Land Use Change Earth Resources Observation and Science (EROS) Center

A look at WorldDEM and Proba V data



Md. Obaidul Haq, Ajit Sampath


Outline

- WorldDEM
 - Data Overview
 - Assessments
 - GCPs from DGPS
 - Lidar
- Proba V
- Summary



WorldDEM Data

- Data in Geographic coordinates
- Minnehaha and Lincoln Counties, SD and Parts of Iowa
- Pixel GSD .0001 degrees
- EGM2008 vertical datum, Units: meters
- Data Projected to UTM, GSD 10 m.






Reference Data

- Post Processed Kinematic GPS Survey
 - Over 75 Locations
 - Collected in Summer 2014 to support data analysis as well as part of EROS 3D Range
 - Flat areas
 - At least 30 m away from vertical structures
- Within 7-12 cm vertical accuracy
- Lidar Data
 - 5 ft Point Spacing
 - About 13 cm vertical accuracy



Reference Data





Tests

- GPS Data used to check elevation in flat areas
- Lidar Data used in sloping areas
 - Good correspondence in heights between Lidar and GPS based points in flat areas
 - Higher Slopes also corresponded with areas of high vegetation
- GDAL and ArcPy used for tests



Results

GPS Points

- Mean: 0.76 m
- Standard Deviation 1.89 m
- RMSE: 2.05 m
- Matches well with WorldDEM specifications of 2 m Relative and 4 m absolute vertical accuracy

Lidar Data

- Similar results to GPS data on Lower Slopes
- Higher slopes in the test area are mainly vegetated
 - Different penetration of Lidar and Radar data into vegetation renders comparison questionable and is excluded for the present
- Note that study area is mostly gently rolling terrain
 - Higher slopes present along river valleys with vegetation



Continuing Work

- Horizontal Resolution Estimation
- Evaluation in high terrain low vegetation areas
- Slope and Aspect Comparisons



Proba V Overview


- Project for On-Board Autonomy (Vegetation) or Proba-V was launched at 6 May 2013
- Objective: to bridge the gap between SPOT-VGT and Sentinel-3 for space borne vegetation measurement

	. -	
Altitude	820 km	
Local overpass time at launch	10:45 h	
Inclination	Sun-Synchronous Orbit	
Coverage	90% daily, 100% every 2 days	
Payload Mass	33.3 kg	
Payload Dimensions	0.2 x 0.8 x 0.35 m ³	
Designed lifetime	2.5 - 5 yr	

Source: Proba-V Products User Manual



Proba-V Instrument Layout



- Field of view: 102⁰ Source: Proba-V Products User Manual
- Swath width: 2295 km
- Number of cameras : 3
- Observation time difference between NIR & SWIR : 12 s
- GSD: VNIR 100m at Nadir 350m at extreme edges
- GSD : SWIR 180m at Nadir 660m at extreme edges



Spectral and Radiometric Characteristics

Band name and centre wavelength (nm)	Band width (nm)	SNR @Lref(W m ⁻² sr ⁻¹ µm ⁻¹)	
BLUE, 463	46	155 @111	
RED, 655	79	430 @110	
NIR, 845	144	529 @106	
SWIR, 1600	73	380 @20	
Radiometric performance			
Absolute accuracy	5%		
Inter-channel accuracy	3%		
Stability	3%		

Source: Proba-V Products User Manual



Scene selection

- Level 1C segment products were used
- Processing steps for L1C
 - Geometric processing
 - Radiometric processing
- Output of radiometric processing is scaled TOA reflectance



Data Extraction

- L1C data are distributed as HDF5 format
- Proba-V Product Customization Tool (PPT) was used to extract band image data
 - Map projection of L1C data was not supported.
- GDAL was used to extract metadata
- ENVI was used for image viewing and analysis
- Continue to Work with Synthesis products to perform detailed Radiometric and Geometric analysis



Geometry

- S1 TOA Products used
- Band 2 Band registration was performed
 - Very well registered bands
- Geolocation could not be satisfactorily performed
 - More Study Needed and Ongoing




SCENE ID: PROBAV_L1C_20140926_084927_3_V001.HDF5

Right Camera



Blue Band


- Hi end saturation observed in cloudy areas
- Hi end saturation value 2047 DN or TOA reflectance of 1.0235





Blue Band


- Sometimes saturated detector response bounces back and forth between two signal levels
 - Usually seen near the edges of clouds
- Several detectors are affected





Red Band

- Hi end saturation observed in cloudy areas
- Hi end saturation value 2047 DN or TOA reflectance of 1.0235
- Sometimes saturated detector response bounces back and forth between two signal levels





SWIR1 Band


 Some detector's responses are slight different than their adjacent detectors causing striping in the image





SWIR1 Band


- Some detector's responses are slight different than their adjacent detectors causing striping in the image
 - Easily visible in homogenous low signal areas






SWIR2 Band

 Some detector's responses are slight different than their adjacent detectors causing striping in the image






Some detector's responses are slight different than their adjacent detectors causing striping in the image





Some detector's responses are slight different than their adjacent detectors causing striping in the

image






Center Camera

SCENE ID: PROBAV_L1C_20140920_092019_2_V001.HDF5



Blue Band

- Hi end saturation observed in cloudy areas
- Hi end saturation value 2047 DN or TOA reflectance of 1.0235



Red Band

Hi end saturation observed in cloudy areas

Hi end saturation value 2047 DN or TOA reflectance


of 1.0235






NIR Band

- Hi end saturation observed in cloudy areas
- Hi end saturation value 2047 DN or TOA reflectance of 1.0235




SWIR1 Band




SWIR1 Band

Striping




SWIR2 Band

Striping



SWIR3 Band

striping



SCENE ID: PROBAV_L1C_20140928_094855_1_V001.HDF5

Left Camera




Blue Band

Hi end saturation observed in cloudy areas

Hi end saturation value 2047 DN or TOA reflectance


of 1.0235





Red Band


- Hi end saturation observed in cloudy areas
- Hi end saturation value 2047 DN or TOA reflectance of 1.0235






NIR Band

- Hi end saturation observed in cloudy areas
 - less common in NIR band
- Hi end saturation value 2047 DN or TOA reflectance of 1.0235



SWIR1 Band


Striping





SWIR3 Band

Striping





Summary

- Limited number of scenes were analyzed
 - One scene from each camera
- Hi end saturation was observed in V-NIR Bands
 - Worst in Blue Band
- Striping was observed in SWIR Bands
 - Usually only few detectors are causing striping
 - Worst in SWIR1 Band
- Future Work
 - Continue to access higher products for further radiometric and Geometric analysis



Summary

- WorldDEM and Proba V Characterizations
- Future Analysis:
 - Continued data assessments for Medium resolution datasets ...
 - Elevation data characterizations
- More data are welcome
- More collaborations welcome

